11/2017 Page 1

Specifications. BMW i8 Coupe.



	BMW i8 Coupe	
Dode		
Body		0.14
No of doors/seats		2/4
Length/width/height (unladen)	mm	4689 / 1942 / 1293
Wheelbase	mm	2800
Track, front/rear	mm	1644 / 1721 117
Ground clearance	mm	12,3
Turning circle	0/ / 0/	
Axle load distribution (unladen) f / r	%/%	49 / 51
Weight, unladen, to DIN/EU Max load to DIN	kg	1535 / 1610 370
	kg	
Height of centre of gravity	mm	< 460
Luggage comp capacity	I	154
Air resistance	CdxA	0.26 x 2.15
Power unit		
Drive concept	Hybrid-specific all-wheel drive: combustion engine sends	
		rear wheels, electric motor sends power to the front wheels
Maximum system output	kW/hp	275 / 374
Petrol engine		
Engine technology		BMW TwinPower Turbo technology:
		Highly turbocharged engine, High Precision Direct Injection,
		VALVETRONIC fully variable valve timing
Config / no of cyls / valves		In-line / 3 / 4
Effective capacity	CC	1499
Stroke / bore	mm	94.6 / 82.0
Compression ratio	:1	9,5
Compression ratio		Min. RON 91
Fuel		Data on rated output and fuel consumption is based on RON 98
Output	kW/hp	170 / 231
at	rpm	5800
Torque	Nm	320
at	rpm	3700
Fuel tank capacity	I I	30, optional: 42
Electric motor Motor technology		BMW eDrive technology:
Wiotor technology		Hybrid synchronous electric motor with power electronics, integrated
		charging module and generator function for energy recuperation
Max output	kW/hp	105 / 143
viax output at	rpm	4800
Rated output	kW/hp	75 / 102
Rated output at		4800
at Torque	rpm Nm	250
Recuperation output	kW	60
·		
High-voltage battery		I Maiore tere
Storage technology		Lithium-ion
Voltage	V	355
Battery cell capacity	Ah	34
Energy capacity (gross)	kWh	11.6
Charging time for 80 % charge		< 2 h at 3.6 kW (16 A / 230 V)
Charging time for 100 % charge	< 3 h at 3.6 kW (16 A / 230 V)	
Charging time for 100 % charge	< 4.5 h from domestic power socket (10 A / 230 V)	

		BMW i8 Coupe
Driving dynamics		
Steering		Electric Power Steering (EPS)
Steering ratio, overall	:1	16.0
Tyres, front/rear		195/50 R20 / 215/45 R20
Rims, front/rear		7J x 20 forged aluminium / 7.5J x 20 forged aluminium
Transmission		
Type of transmission: co engine		6-speed automatic
Type of transmission: el motor	ectric	2-speed automatic
Performance		
Power-to-weight ratio (D	DIN) kg/kW	5.6
Output per litre: petrol e		113.3
Acceleration 0-100) km/h s	4.4
80–12	20 km/h s	2.6
in 4th/5th gear 80–12	20 km/h s	3.4 / 4.0
Top speed	km/h	250 (electronically governed)
Top speed (electric)	km/h	120
Total range*	km	440 (600 with optional 42-litre tank)
Electric range*	km	(<mark>55</mark>)
Fuel consumption / e in the EU cycle*	missions	
Fuel consumption comb	pined I/100 km	1.9
CO ₂ emissions combine		42
Electricity consumption		14.0
Emission rating		EU6

Provisional specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

wheels/tyres and the selected items of optional equipment.

The values are already based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. [With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).]

The CO_2 efficiency specifications are determined according to Directive 1999/94/EC and the latest version of the Pkw-EnVKV, and based (for classification) on the fuel consumption and CO_2 values as per the NEDC cycle. Further information on official fuel consumption figures and specific CO_2 emission values of new passenger cars is included in the following guideline: "Leitfaden über den Kraftstoffverbrauch, die CO_2 -Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guideline for fuel consumption, CO_2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships and at https://www.dat.de/en/offers/publications/guideline-for-fuel-consumption.html.

^{*}The fuel consumption, CO₂ emissions, power consumption and operating range figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected